SPLIT SYSTEMS FOR SHUTTLE AND SCHOOL BUSES

TROPICOOL

SKIRT MOUNTED CONDENSER



PERFORMANCE, RELIABILITY & LOOKS

Valeo provides the best performance and reliability for the application your vehicle requires by manufacturing several different condenser designs. Certain applications provide a more aesthetic OEM look to the bus by eliminating the need to cut intakes in the skirt of the bus.



SKIRT MOUNTED CONDENSERS

HIGHLIGHTS



Design

- · Designed to be skirt mounted
- High performance motors with extended brush life
- Fabricated from galvannealed steel & covered in corrsion resistant epoxy for durability
- Inlet filter on condenser protects coil from contaminants




Environmental Friendliness

- High performance parallel flow condenser
- Highly efficient all aluminum micro channel coil



Features


- 1, 2 or 3 11" diameter high perfor mance fans or two 14" diamter fans covering a larger percentage of sur face area on condenser coil
- Easy Installation without having to cut intakes in skirt of busschool bus



25059



25060



25073



25065



25062



25063

TECHNICAL DATA

| Model | Up to Cooling Capacity | Power Consumption | Nominal Voltage | Dimensions W x H x D | Weight |
|------------|------------------------|----------------------|--------------------|----------------------|---------|
| 25059-3fan | 100,000 BTU/h | 25 Amps | 12V | 39 x 7 x 20 in | 56 lbs. |
| 25060-2fan | 100,000 BTU/h | 22 Amps | 12V | 39 x 7 x 20 in | 56 lbs. |
| 25073-3fan | 83,000 BTU/h | 25 Amps | 12V | 37 x 3 x 16 in | 51 lbs. |
| 25065-2fan | 83,000 BTU/h | 22 Amps | 12V | 37 x 3 x 16 in | 51 lbs. |
| 25074-3fan | 78,000 BTU/h | 25 Amps | 12V | 39 x 7 x 16 in | 60lbs. |
| 25049-2fan | 78,000 BTU/h | 22 Amps | 12V | 39 x 7 x 16 in | 60 lbs. |
| 25062 | 67,000 BTU/h | 18 Amps | 12V | 30 x 5 x 14 in | 26 lbs. |
| 25063 | 40,000 BTU/h | 9 Amps | 12V | 30 x 5 x 14 in | 22 lbs |

